



DETAIL G
SCALE 1 : 12

DETAIL A
SCALE 1 : 4

Mounting Hole Location

Size	A	B
1x4	38"	8"
2x2	14"	18"
2x4	38"	18"

INSTRUCTIONS: --> **NOTE:** FOR ADDITIONAL INFORMATION, REFER TO IIS00035 <--

1. Provide ceiling cut-out at 24-3/8" x 48-3/8" (2x4), 24-3/8" x 24-3/8" (2x2), 12-3/8" x 48-3/8" (1x4)
2. Provide appropriate beam structure to support fixture.
3. Install threaded bolt from ceiling structure above ceiling, using same spacing as mounting holes on fixture. Guide fixture up into cutout, guiding threaded bolt into 5/16" ϕ mounting holes in fixture. Install washers and nuts to hold fixture.
4. Replace fixture covers and close up the door.
5. It may be useful to remove the door from the cable for the process and re-attach after it is complete.

	NAME	DATE			
Drawn	FBottoni				
Last Saved	f.b.	05-28-2020	ERP #:	IIS00114	
Checked			REVISION:	03	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MANUFACTURER ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MANUFACTURER IS PROHIBITED.	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES ANGULAR: BEND ± 1 ONE PLACE DECIMAL ± 0.030 TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		Title: Part Name: VRF3553 Description: 3553 VRF INSTALLATION INSTRUCTION		
	MATERIAL:		FINISH: NONE		
	SIZE: A	SCALE:			
				SHEET 1 of 1	